

Material Lifts

Super Hoist[™]

Specifications

Models	GH-3.8		GH-5.6	
Measurements	Metric	US	Metric	US
▲ Height - stowed - lifting height	1.04 m 3.80 m	3 ft 5 in 12 ft 5.6 in	1.37 m 5.60 m	4 ft 6 in 18 ft 4.5 in
▲ Length - platform	48 cm	1 ft 7 in	48 cm	1 ft 7 in
▲ Width - platform	61 cm	2 ft	61 cm	2 ft
 base (corner to corner) 	1.35 m	4 ft 5 in	1.35 m	4 ft 5 in

Productivity

Load capacity	136 kg	300 lbs	113 kg	250 lbs
Storage/transport dimensions	36 cmx36 cmx1 m	14x14x39.5 in	36 cmx36 cmx1 m	14x14x39.5 in
Wheels, solid non-marking	20 cm diam.	8 in diam.	20 cm diam.	8 in diam.

Power


Recommended PSI	5.86 bar	85 psi	5.86 bar	85 psi

Weight

gi it					
	34 kg	75 lbs	37 kg	82 lbs	

Standards Compliance

EU Directive: 2006/42/EC (Machinery)



www.genielift.co.uk www.genielift.me



Material Lifts

Super Hoist™

Features

Standard Features

Measurements

GH™-3.8

- 3.80 m (12 ft 5.6 in) lifting height
- 136 kg (300 lbs) load capacity

- 5.60 m (18 ft 4.5 in) lifting height
- 113 kg (250 lbs) load capacity

Productivity

- Portable and compact design
- Up and down dump valve can be easily activated by patented control handle
- The Super Hoist sets up in seconds - no tools required
- The one-piece platform attaches to cylinder with a twist of the wrist
- · Legs fold up for easy storage
- Easy-to-release leg lock keeps legs up for storage and out for use
- Wheel brakes
- Auto-lubricating oil reservoir on top of each piston inside the cylinder
- Easy to service

Power

- Powered by CO₂ or compressed air
- One size fits all CO bottle mounting bracket

Easily Configured To Meet Your Needs

Platform

One-piece platform

Base Options

- GH 3.8
- GH 5.6

Wheels

• Solid, non-marking, 20 cm (8 in) diameter (standard)

Options & Accessories

Productivity

Platform cradle package









Jøma Lift Teknik A/S

Nordager 24, DK 6000 Kolding, Denmark. Tel: +45 75864333 Email: info@genielift.dk www.Genielift.dk

Worldwide Manufacturing And Distribution

Australia - Brazil - Caribbean - Central America - China - France - Germany - Italy - Japan - Korea - Mexico - Russia - Southeast Asia - Spain - Sweden - United Arab Emirates - United Kingdom - United States

uct specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate ator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and ose listed maybe trademarks, service marks or trade anases of Terex Corporation and/or their subsidiaries in the USA and rother countries. Gene is a registered trademark of Terex South Daksch, Inc. @ 2015 Terex Corporation.