


# Aerial Work Platforms

## IWP™ Super Series™

### Specifications



Models	IWP-20S		IWP-25S		IWP-30S	
Measurements	Metric	US	Metric	US	Metric	US
Working height*	8.15 m	26 ft 2 in	9.44 m	30 ft 5 in	11 m	35 ft 6 in
Platform height	6.15 m	20 ft 2 in	7.44 m	24 ft 5 in	9 m	29 ft 6 in
▲ Horizontal outreach**	66 cm	2 ft 2 in	---	---	---	---
▲ Height - stowed:						
fully lowered	1.93 m	6 ft 4 in	1.93 m	6 ft 4 in	1.93 m	6 ft 4 in
base raised	1.98 m	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m	6 ft 6 in
▲ Length	1.52 m	5 ft	1.52 m	5 ft	1.52 m	5 ft
▲ Width - standard base	81 cm	2 ft 8 in	81 cm	2 ft 8 in	---	---
wide base	---	---	---	---	1.02 m	3 ft 4 in
Corner access***	15 cm	6 in	15 cm	6 in	18 cm	7 in

### Productivity

Lift capacity	159 kg	350 lbs	159 kg	350 lbs	159 kg	350 lbs
Platform Dimensions (l/w/h)						
Standard	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in
Gated standard	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in
Gated narrow	66/51/114 cm	26/20/44.75 in	66/51/114 cm	26/20/44.75 in	66/51/114 cm	26/20/44.75 in
Standard fiberglass**	74/67/110 cm	29/26.5/43.5 in	74/67/110 cm	29/26.5/43.5 in	74/67/110 cm	29/26.5/43.5 in

### Power

AC models	110 V / 50-60 Hz or 220 V / 50-60 Hz
DC models	12V

### Sound & Vibration Levels

Sound pressure level (ground workstation)	<70 dBA	<70 dBA	<70 dBA	<70 dBA	<70 dBA	<70 dBA
Sound pressure level (platform workstation)	<70 dBA	<70 dBA	<70 dBA	<70 dBA	<70 dBA	<70 dBA
Vibration	<2.5 m/s <sup>2</sup>	<8 ft 2 in/s <sup>2</sup>	<2.5 m/s <sup>2</sup>	<8 ft 2 in/s <sup>2</sup>	<2.5 m/s <sup>2</sup>	<8 ft 2 in/s <sup>2</sup>

### Weight\*\*\*\*

<b>Standard base</b>						
AC	565 kg	1,245 lbs	585 kg	1,290 lbs	---	---
DC	610 kg	1,345 lbs	630 kg	1,390 lbs	---	---
<b>Standard base with outreach option</b>						
AC	612 kg	1,350 lbs	---	---	---	---
DC	658 kg	1,450 lbs	---	---	---	---
<b>Wide base</b>						
AC	---	---	---	---	649 kg	1,430 lbs
DC	---	---	---	---	694 kg	1,530 lbs

### Standards Compliance

EU Directives: 2006/42/EC - Machinery (harmonized standard EN280:2013); 2004/108/EC (EMC); 2006/95/EC (LVD)

\* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.

\*\* Fiberglass platforms are not available with the outreach option.

\*\*\* Corner of platform top rail to corner of wall with ability to rotate leveling jack handle.

\*\*\*\* Weight will vary depending on options and/or country standards.

### Features

#### Standard Features

##### Measurements

###### IWP-20S

- 8.24 m (26 ft 6 in) working height
- 6.24 m (20 ft 6 in) platform height
- 81 cm (2 ft 8 in) standard base width
- Outreach option adds 66 cm (2 ft 2 in) of horizontal reach
- Up to 159 kg (350 lbs) lift capacity

###### IWP-25S

- 9.44 m (30 ft 5 in) working height
- 7.44 m (24 ft 5 in) platform height
- 81 cm (2 ft 8 in) standard base width
- Up to 159 kg (350 lbs) lift capacity

###### IWP-30S

- 11 m (35 ft 6 in) working height
- 9 m (29 ft 6 in) platform height
- 1.02 m (3 ft 4 in) wide base width
- Up to 159 kg (350 lbs) lift capacity

##### Productivity

- Auxiliary platform lowering
- Most rigid mast in the industry
- Standard base rolls through standard doorways
- Wide base rolls through double doorways
- AC power to platform
- Dual activated up/down switch
- Tie down attachment points
- Overhead crane attachment point
- Wide forklift pockets
- Built-in level sensing with interlocks

#### Easily Configured To Meet Your Needs

##### Platform Options

- Sliding mid-rail platform (standard)
- Gated standard platform
- Gated narrow platform
- Standard fiberglass platform (not available with outreach)

##### Power Options

- AC power 85V / 50-60 Hz
- AC power 110V / 50-60 Hz
- AC power 220V / 50-60 Hz
- DC power with worldwide automatic "smart" charging system (12V / 110V / 230V / 50-60 Hz)

##### Base Options

- Standard base (IWP-20S and 25S only)
- Wide base (IWP-30S only)

#### Options & Accessories

##### Productivity

- Outreach option (IWP-20S only)<sup>(3)</sup>
- Power to platform (plug, socket and ground fault interrupt leakage on request)
- Operational warning light and descent alarm package
- Tool tray<sup>(1)</sup>
- Fluorescent tube caddy<sup>(1)</sup>
- Platform locating laser light<sup>(1)</sup>

##### Power

- Power wheel assist with dual battery package<sup>(2) (3)</sup>
- Dual battery package<sup>(3)</sup>



<sup>(1)</sup> Available on selected models only. See your Genie representative for further information.

<sup>(2)</sup> Adds 32 cm (12.5 in) to unit length and 129 kg (285 lbs) to unit weight.

<sup>(3)</sup> Factory-fit option only.