


Solid and stable

	LEGUAN 165
SWL for the entire working area	230 kg / 2 persons
Max. working height	16.40 m
Max. platform height	14.40 m
Max. outreach	7.85 m
Transport length	5.01 m
Platform dimensions W x L	1.33 x 0.75 m
Rotation of basket	90° (±45°)
Slewing	360°
Gradeability	50% (27°)
Outrigger support dimensions	3.78 x 3.83 m
Max. slope for outriggers	22% (I3°)
Weight with tracks / tyres	2530 kg/2530 kg
Power source	Kubota 14 hp diesel
	230 V / 110 V*
Drive system: hydraulic	4WD
	Tracks*
Drive speed max.	2,6 km/h (5,2 km/h*)

- * Optional item
- Robust three boom design
- **Direct hydraulic controls**
- Active weight control
- Ground contact sensing outrigger control
- **Telescopic boom**
- Negative jib boom (120 deg.)
- High platform capacity over whole working area
- Excellent maneuverability next to a wall, straight vertical lifting up to 11 m
- Improved drive comfort and reduced tremor with tracks
- Stable and soft boom movements
- **Inductive limit switches**
- PCB with light indicated relay controls
- Work lights at the work cage (optional item)









Leguan has a policy of continuing improvement, and retains the right to change specifications without notice. © 2019 LEGUAN Lifts Oy. All rights reserved.